



**A.SHORT LINK CHAIN (DIN 766)**

Part No. 316	Size (D) mm	P mm	B mm	Wgt. KG/M	Breaking Strain
<b>6920</b>	M2*	22.00	8.00	0.16	150 Kg
<b>16915</b>	M3	16.00	11.00	0.16	800 Kg
<b>6921</b>	M4	16.00	14.00	0.32	1350 Kg
<b>16916</b>	M5	18.50	17.00	0.50	1970 Kg
<b>6922</b>	M6	18.50	20.00	0.75	2880 Kg
<b>6923</b>	M8	24.00	26.00	1.35	5100 Kg
<b>6924</b>	M10	28.00	34.00	2.25	7900 Kg

\* M2 IS DIN 763

**B.MEDIUM LINK CHAIN**

Part No. 316	Size (D) mm	P mm	B mm	Wgt. KG/M	Breaking Strain
<b>43998</b>	M2	12.00	8.00	0.10	280 Kg
<b>43999</b>	M3	16.00	12.00	0.16	450 Kg
<b>44000</b>	M4	19.00	16.00	0.30	800 Kg
<b>44001</b>	M5	21.00	20.00	0.45	1200 Kg
<b>44002</b>	M6	24.00	24.00	0.70	1800 Kg
<b>44003</b>	M8	32.00	32.00	1.30	3200 Kg
<b>44004</b>	M10	40.00	40.00	2.00	5000 Kg
<b>44005</b>	M12	48.00	48.00	2.90	7200 Kg